



SLINE

| | | | | | |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
| Item code | 86.L001.4403.02 | | | | |
| Product type | Indoor | | | | |
| Category | Linear Systems | | | | |
| Family | SLINE | | | | |
| Pictograms | <div><div></div><div>220 240 V</div><div>CRI 80</div><div>CE</div><div>Driver INCL.</div></div> <div><div>On Off</div><div> 1-10V</div><div>IP 20</div><div>50000h L80B10</div></div> | | | | |

| | |
|-------------------------|--------------|
| Dimensions | |
| Product dimensions (mm) | 50x75X2400mm |

| | |
|--------|--|
| Scheme | |
| | |

| | |
|----------------------------|---------------|
| Product | |
| Real power (W) | 80 |
| Real luminous flux (Lm) | 8000 |
| Luminous efficiency (Lm/W) | 100 |
| Beam angle (°) | 110 |
| Life time (h) | 50000h L80B10 |
| IP | 20 |
| U. G. R | 22 |
| Control gear | DALI |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |