



ZENITH IP65S Trimless

|              |                                                                                                                                                                                                       |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item code    | 86.D087.2431.02                                                                                                                                                                                       |
| Product type | Indoor                                                                                                                                                                                                |
| Category     | Downlights                                                                                                                                                                                            |
| Family       | ZENITH                                                                                                                                                                                                |
| Subfamily    | ZENITH IP65S Trimless                                                                                                                                                                                 |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div></div><div>CRI<br/>90</div><div>CE</div><div>Driver<br/>INCL</div><div>On<br/>Off</div><div></div><div>50000h<br/>L80B10</div><div>IP<br/>65</div></div> |

Dimensions

Product dimensions (mm) 94\*94\*146mm

Scheme



Product

|                            |                |
|----------------------------|----------------|
| Real power (W)             | 30             |
| Real luminous flux (Lm)    | 2400           |
| Luminous efficiency (Lm/W) | 80             |
| Beam angle (°)             | 36             |
| Life time (h)              | 50000 h L80B10 |
| IP                         | 65             |
| U. G. R                    | 19             |
| Control gear               | ON/OFF         |
| Colour temperature (K)     | 4000           |
| Colour consistency (SDCM)  | SDCM<3         |
| CRI                        | 90             |