



ZENITH IP65R Smart Trimless

|              |   |
|--------------|---|
| Item code    | 86.DS86.2349.01   |
| Product type | Indoor  |
| Category     | Downlights  |
| Family       | ZENITH  |
| Subfamily    | ZENITH IP65R Smart Trimless   |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div></div><div>CRI<br/>90</div><div>CE</div><div>Driver<br/>INCL</div><div>On<br/>Off</div><div></div><div>50000h<br/>L80B10</div><div>IP<br/>65</div></div> |

Dimensions

|                         |            |
|-------------------------|------------|
| Product dimensions (mm) | Φ115*130mm |
| Packing dimensions (mm) | Φ115*110mm |

Scheme



|                            |                       |
|----------------------------|-----------------------|
| Product                    |                       |
| Real power (W)             | 30                    |
| Real luminous flux (Lm)    | 2400                  |
| Luminous efficiency (Lm/W) | 80                    |
| Beam angle (°)             | 60                    |
| Life time (h)              | 50000 h L80B10        |
| IP                         | 65                    |
| U. G. R                    | 19                    |
| Control gear               | DALI+wireless Casambi |
| Colour temperature (K)     | 3000                  |
| Colour consistency (SDCM)  | SDCM3                 |
| CRI                        | 80                    |

Photometry

