



Micro 5

|              |                                                                                                                                                                                                           |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item code    | 86.T001.1413.01                                                                                                                                                                                           |
| Product type | Indoor                                                                                                                                                                                                    |
| Category     | Tracklights                                                                                                                                                                                               |
| Family       | Micro                                                                                                                                                                                                     |
| Subfamily    | Micro 5                                                                                                                                                                                                   |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div></div><div>CRI<br/>90</div><div>CE</div><div>Driver<br/>INCL</div><div>On<br/>Off</div><div>DALI</div><div>IP<br/>20</div><div>50000h<br/>L80B10</div></div> |

Scheme



|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 12            |
| Real luminous flux (Lm)    | 1200          |
| Luminous efficiency (Lm/W) | 100           |
| Beam angle (°)             | 12            |
| Life time (h)              | 50000h L80B10 |
| IP                         | 20            |
| Operating temperature      | -20 +35       |
| Control gear               | DALI          |
| Colour temperature (K)     | 4000          |
| Colour consistency (SDCM)  | SDCM3         |
| CRI                        | 90            |

Photometry

