







TUBULAR-S

|              |   |  |  |  |  |
|--------------|---|--|--|--|--|
| Item code    | 86.SD01.2343.01   |  |  |  |  |
| Product type | Indoor  |  |  |  |  |
| Category     | Surface Downlights  |  |  |  |  |
| Family       | TUBULAR-S   |  |  |  |  |
| Pictograms   | <div><div></div><div><div>220<br/>240 V</div></div><div></div><div><div>CRI<br/>80</div></div><div></div></div> <div><div>On<br/>Off</div><div></div><div><div>50000h<br/>L80B10</div></div><div><div>IP<br/>65</div></div></div> |  |  |  |  |

|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 20            |
| Real luminous flux (Lm)    | 1600          |
| Luminous efficiency (Lm/W) | 80            |
| Beam angle (&ordm;)        | 60            |
| Life time (h)              | 50000h L80B10 |
| IP                         | IP65          |
| Control gear               | DALI          |
| Colour temperature (K)     | 3000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |

Dimensions

Product dimensions (mm) Ø95X152 mm

Scheme



Photometry

