



C-SLINE

|              |                 |              |           |                  |                 |
|--------------|-----------------|--------------|-----------|------------------|-----------------|
| Item code    | 86.L004.6301.02 |              |           |                  |                 |
| Product type | Indoor          |              |           |                  |                 |
| Category     | Linear Systems  |              |           |                  |                 |
| Family       | C-SLINE         |              |           |                  |                 |
| Pictograms   |                 | 220<br>240 V | CRI<br>80 | CE               | Driver<br>INCL. |
|              | On<br>Off       | 1-10V        | IP<br>20  | 50000h<br>L80B10 |                 |

|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 185           |
| Real luminous flux (Lm)    | 15725         |
| Luminous efficiency (Lm/W) | 85            |
| Beam angle (°)             | 108           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 40            |
| U. G. R                    | 22            |
| Control gear               | ON-OFF        |
| Average life time (h)      | 50000h L80B10 |
| Colour temperature (K)     | 3000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |

Dimensions

Product dimensions (mm)  $\Phi 3000\text{mm} \times W50\text{mm} \times H70\text{mm}$

Scheme

