



MINIPPOINT-A

|              |                                                                                                                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item code    | 86.D019.3333.02                                                                                                                                                                                 |
| Product type | Indoor                                                                                                                                                                                          |
| Category     | Downlights                                                                                                                                                                                      |
| Family       | MINIPPOINT                                                                                                                                                                                      |
| Subfamily    | MINIPPOINT-A                                                                                                                                                                                    |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div>CRI<br/>80</div><div>CE</div><div>Driver<br/>INCL.</div><div>On<br/>Off</div><div>DALI</div><div>IP<br/>20</div><div>50000h<br/>L80B10</div></div> |

Scheme



|                            |                |
|----------------------------|----------------|
| Product                    |                |
| Real power (W)             | 9              |
| Real luminous flux (Lm)    | 630            |
| Luminous efficiency (Lm/W) | 70             |
| Beam angle (°)             | 40             |
| Life time (h)              | 50000 h L80B10 |
| IP                         | 20             |
| Control gear               | DALI           |
| Colour temperature (K)     | 3000           |
| Colour consistency (SDCM)  | SDCM<3         |
| CRI                        | 80             |