



B-PANEL

|              |  |  |  |  |  |
|--------------|--|--|--|--|--|
| Item code    | 86.R002.1403.01  |  |  |  |  |
| Product type | Indoor   |  |  |  |  |
| Category     | Recessed Fixtures  |  |  |  |  |
| Family       | B-PANEL  |  |  |  |  |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div></div><div>850°</div><div>CRI<br/>80</div><div>CE</div><div>Driver<br/>INCL</div><div>On<br/>Off</div><div>DALI</div><div>IP<br/>20</div><div>50000h<br/>L80B10</div></div> |  |  |  |  |

|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 30            |
| Real luminous flux (Lm)    | 3840          |
| Luminous efficiency (Lm/W) | 128           |
| Beam angle (°)             | 120           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 20 / 40       |
| Chip Brand                 | Seoul         |
| Control gear               | DALI          |
| Colour temperature (K)     | 4000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |

|                         |            |
|-------------------------|------------|
| Dimensions              |            |
| Product dimensions (mm) | 596x596x35 |
| Scheme                  |            |

