



MLINER

|              |                 |
|--------------|-----------------|
| Item code    | 86.LR02.2402.02 |
| Product type | Indoor          |
| Category     | Linear Systems  |
| Family       | MLINER          |

|            |           |              |           |                  |                 |
|------------|-----------|--------------|-----------|------------------|-----------------|
| Pictograms |           | 220<br>240 V | CRI<br>80 | CE               | Driver<br>INCL. |
|            | On<br>Off | 1-10V        | IP<br>20  | 50000h<br>L80B10 |                 |

|                         |                   |
|-------------------------|-------------------|
| Dimensions              |                   |
| Product dimensions (mm) | L1215xW90xH35mmmm |

|        |  |
|--------|--|
| Scheme |  |
|        |  |

|            |  |
|------------|--|
| Photometry |  |
|            |  |

|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 36            |
| Real luminous flux (Lm)    | 3600          |
| Luminous efficiency (Lm/W) | 100           |
| Beam angle (°)             | 110           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 20            |
| U. G. R                    | 22            |
| Control gear               | 0-10V Dim     |
| Colour temperature (K)     | 4000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |