




BEAM MODULES

| | |
|--------------|--|
| Item code | 86.OS01.3351.02 |
| Product type | Outdoor |
| Category | Spike Spot Light |
| Family | BEAM |
| Subfamily | BEAM MODULES |
| Pictograms | <div><div></div><div>220 240 V</div><div></div><div>850°</div><div>CRI 80</div><div>SDCM 3</div></div> <div><div></div><div>Driver INCL.</div><div>On Off</div><div></div><div></div></div> <div><div>50000h L70B10</div><div>IP 65</div><div></div><div>335°</div><div></div><div>90°</div><div>IK 05</div></div> |


Dimensions

Product dimensions (mm) 170(Dia)X101(H)mm

Scheme



Photometry



| | |
|----------------------------|---------------|
| Product | |
| Real power (W) | 36 |
| Real luminous flux (Lm) | 2450 |
| Luminous efficiency (Lm/W) | 68 |
| Beam angle (°) | 60 |
| Life time (h) | 50000h L70B10 |
| IP | 66 |
| Chip Brand | Osram |
| Control gear | ON-OFF |
| Average life time (h) | 50000h L70B10 |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM3 |
| CRI | 80 |
| IK | IK08 |