



LINEAR

| | | | | | | | |
|--------------|--|--|--|--|--|--|--|
| Item code | 86.OIN8.2331.03 | | | | | | |
| Product type | Outdoor | | | | | | |
| Category | Recessed Inground Floor | | | | | | |
| Family | LINEAR | | | | | | |
| Pictograms | <div><div></div><div>50 60 Hz</div><div>220 240 V</div><div></div><div>IK 10</div><div>CRI 80</div><div>SDCM 3</div><div>CE</div><div>Driver INCL.</div><div>On Off</div><div></div><div>50000h L80B10</div><div>IP 67</div></div> | | | | | | |

Dimensions

Product dimensions (mm) 55x80x1000mm

Scheme



| | |
|----------------------------|---------------|
| Product | |
| Real power (W) | 48 |
| Real luminous flux (Lm) | 2780 |
| Luminous efficiency (Lm/W) | 58 |
| Beam angle (°) | 30 |
| Life time (h) | 50000h L80B10 |
| IP | 67 |
| Control gear | ON-OFF |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM3 |
| CRI | 80 |
| IK | IK10 |

Photometry

RECESSED INGROUND FLOOR -
LINEAR

Item code 86.OIN8.2331.03

