




STAR-A Smart

|              |   |  |  |  |  |
|--------------|---|--|--|--|--|
| Item code    | 86.DS31.2329.01   |  |  |  |  |
| Product type | Indoor  |  |  |  |  |
| Category     | Downlights  |  |  |  |  |
| Family       | STAR  |  |  |  |  |
| Subfamily    | STAR-A Smart  |  |  |  |  |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div>CRI<br/>90</div><div>CE</div><div>Driver<br/>INCL.</div></div> <div><div>On<br/>Off</div><div></div><div>IP<br/>20</div><div>50000h<br/>L80B10</div></div> |  |  |  |  |

Scheme



|                            |                       |
|----------------------------|-----------------------|
| Product                    |                       |
| Real power (W)             | 4                     |
| Real luminous flux (Lm)    | 240                   |
| Luminous efficiency (Lm/W) | 60                    |
| Beam angle (°)             | 30                    |
| Life time (h)              | 50000 h L80B10        |
| IP                         | 20                    |
| Control gear               | DALI+wireless Casambi |
| Colour temperature (K)     | 3000                  |
| Colour consistency (SDCM)  | SDCM<3                |
| CRI                        | 80                    |