



Quadro

|              |  |  |  |  |  |
|--------------|--|--|--|--|--|
| Item code    | 86.OSP4.1311.03  |  |  |  |  |
| Product type | Outdoor  |  |  |  |  |
| Category     | Spike Spot Light   |  |  |  |  |
| Family       | Quadro   |  |  |  |  |
| Subfamily    | Quadro   |  |  |  |  |
| Pictograms   | <div><div></div><div>220<br/>240 V</div><div></div><div>850°</div><div>CRI<br/>80</div><div>SDCM<br/>3</div></div> <div><div></div><div>Driver<br/>INCL.</div><div>On<br/>Off</div><div></div><div></div></div> <div><div>50000h<br/>L70B10</div><div>IP<br/>65</div><div></div><div>335°</div><div></div><div>90°</div><div>IK<br/>05</div></div> |  |  |  |  |

Scheme



|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 24            |
| Real luminous flux (Lm)    | 1920          |
| Luminous efficiency (Lm/W) | 80            |
| Beam angle (°)             | 15            |
| IP                         | 66            |
| Control gear               | ON-OFF        |
| Average life time (h)      | 50000h L70B10 |
| Colour temperature (K)     | 3000          |
| Colour consistency (SDCM)  | SDCM3         |
| CRI                        | 80            |
| IK                         | IK08          |