



---

---

**Dimensions**

---

|                                |                      |
|--------------------------------|----------------------|
| <b>Product dimensions (mm)</b> | <b>diam 83x131mm</b> |
|--------------------------------|----------------------|

---

---

---

**Scheme**



SDOWN

|              |                           |
|--------------|---------------------------|
| Item code    | 86.OC02.1331.03           |
| Product type | Outdoor                   |
| Category     | Surface Ceiling Downlight |
| Family       | SDOWN                     |

|            |           |             |                 |      |                  |
|------------|-----------|-------------|-----------------|------|------------------|
| Pictograms |           | 50<br>60 Hz | 220<br>240 V    | 850° | CRI<br>80        |
|            | SDCM<br>3 | CE          | Driver<br>INCL. |      | 50000h<br>L80B10 |
|            | IP<br>65  | IK<br>06    |                 |      |                  |

|                            |               |
|----------------------------|---------------|
| Product                    |               |
| Real power (W)             | 15            |
| Real luminous flux (Lm)    | 1150          |
| Luminous efficiency (Lm/W) | 76.67         |
| Beam angle (°)             | 40°           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 65            |
| Chip Brand                 | Osram         |
| Control gear               | ON-OFF        |
| Colour temperature (K)     | 3000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | >80           |
| IK                         | IK06          |