



## **OFFICE**

Lavov architectural luminaire from the family OFFICE with a power of 70.0 (50,0  $\uparrow$  / 20,0  $\downarrow$  )W and a beam angle of  $\uparrow$  112  $^{\circ}$   $\downarrow$  $75^{\circ}$  . UGR10. Finished in black colour. With a total lumen output of  $7300 \text{Im} \uparrow / 2500 \text{Im} \downarrow \text{Im}$  and a luminous efficacy of 140 Im/W. Made in Aluminium housing and pole, steel foot and micro reflector optics. Driver 1-10V. Motion sensor and daylight sensor included.. CCT 3000K.

Dimensions	
Product dimensions (mm)	1225*65*1968mm

Product dimensions (mm)	1225*65*1968mm	

Item code	86.A0010.1392.02 Indoor Architectural luminaires A WORKSTATION	
Product type		
Category		
Family		
Subfamily	OFFICE	
Pictograms	( cRi SDCM 3 C€	
	Driver INCL. 1-10V	

88 <del>3</del>	······
% <b></b> ₹	
<u> </u>	
: H	
	:
	961
	996
225	
7	
÷	<del></del>
338	585

Product	
Real power (W)	70.0 (50,0↑ / 20,0↓)
Real luminous flux (Lm)	7300lm↑ / 2500lm↓
Luminous efficiency (Lm/W)	140
Beam angle (º)	↑ 112°↓ 75°
Colour	black
U. G. R	<10
Control gear included	yes
Control gear	1-10V. Motion sensor and daylight sensor included.
Power Factor	>0.9
Flicker Free	yes
Average life time (h)	L80 B20, 50,000hrs
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80

Scheme