




**OFFICE**

Lavov architectural luminaire from the family OFFICE with a power of 70.0 (50,0↑ / 20,0↓)W and a beam angle of ↑ 112° ↓ 75° . UGR10. Finished in grey colour. With a total lumen output of 7300lm↑ / 2500lm↓lm and a luminous efficacy of 140lm/W. Made in Aluminium housing and pole, steel foot and micro reflector optics. Driver 1-10V. Motion sensor and daylight sensor included.. CCT 4000K.

<b>Item code</b>	<b>86.A0010.1492.03</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Architectural luminaires</b>
<b>Family</b>	<b>WORKSTATION</b>
<b>Subfamily</b>	<b>OFFICE</b>
<b>Pictograms</b>	

<b>Product</b>	
<b>Real power (W)</b>	<b>70.0 (50,0↑ / 20,0↓)</b>
<b>Real luminous flux (Lm)</b>	<b>7300lm↑ / 2500lm↓</b>
<b>Luminous efficiency (Lm/W)</b>	<b>140</b>
<b>Beam angle (°)</b>	<b>↑ 112° ↓ 75°</b>
<b>Colour</b>	<b>grey</b>
<b>U. G. R</b>	<b>10</b>
<b>Control gear included</b>	<b>yes</b>
<b>Control gear</b>	<b>1-10V. Motion sensor and daylight sensor included.</b>
<b>Power Factor</b>	<b>&gt;0.9</b>
<b>Flicker Free</b>	<b>yes</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>SMD</b>
<b>Average life time (h)</b>	<b>L80 B20, 50,000hrs</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM3</b>

CRI

80



---

---

**Dimensions**

**Product dimensions (mm)**      **1225\*65\*1968mm**

---

---

**Scheme**

