



### CLEAR

Lavov architectural luminaire from the family CLEAR with a power of 75W and an optics 343o degrees beam angle with UGR22. CCT 3000K. With a total lumen output of 7500lm and an efficacy of 100lm/W . Made in Edgelit LED, PMMA light guide panel, fine textured powder coated aluminium case and finished in white color. ON-OFF driver.

### Dimensions

Product dimensions (mm) **340x40x1500**

### Scheme



|              |                                 |
|--------------|---------------------------------|
| Item code    | <b>86.A008.2331.01</b>          |
| Product type | <b>Indoor</b>                   |
| Category     | <b>Architectural luminaires</b> |
| Family       | <b>CLEAR</b>                    |
| Pictograms   |                                 |

|                            |                           |
|----------------------------|---------------------------|
| <b>Product</b>             |                           |
| Real power (W)             | <b>75</b>                 |
| Real luminous flux (Lm)    | <b>7500</b>               |
| Luminous efficiency (Lm/W) | <b>100</b>                |
| Beam angle (°)             | <b>343o</b>               |
| Colour                     | <b>white</b>              |
| U. G. R                    | <b>22</b>                 |
| Control gear included      | <b>yes</b>                |
| Control gear               | <b>ON-OFF</b>             |
| Power Factor               | <b>&gt;0,95</b>           |
| Flicker Free               | <b>yes</b>                |
| Light source               | <b>LED</b>                |
| Type of LED                | <b>SMD</b>                |
| Average life time (h)      | <b>L80 B20, 50,000hrs</b> |
| Colour temperature (K)     | <b>3000K</b>              |
| Colour consistency (SDCM)  | <b>SDCM3</b>              |
| CRI                        | <b>80</b>                 |