



### WORKSTATION TABLE

Lavov architectural luminaire from the family WORKSTATION TABLE with a power of 70.0 (35,0↑ / 35,0↓)W and an optics 120°↑ / 120°↓ degrees beam angle with UGR

|                     |                                 |
|---------------------|---------------------------------|
| <b>Item code</b>    | <b>86.A009.2392.01</b>          |
| <b>Product type</b> | <b>Indoor</b>                   |
| <b>Category</b>     | <b>Architectural luminaires</b> |
| <b>Family</b>       | <b>WORKSTATION</b>              |
| <b>Subfamily</b>    | <b>WORKSTATION TABLE</b>        |

#### Pictograms



#### Product

|                                   |   |
|-----------------------------------|---|
| <b>Real power (W)</b>             | <b>70.0 (35,0↑ / 35,0↓)</b>                               |
| <b>Real luminous flux (Lm)</b>    | <b>4200lm↑ / 4200lm↓</b>                                  |
| <b>Luminous efficiency (Lm/W)</b> | <b>120</b>  |
| <b>Beam angle (°)</b>             | <b>120°↑ / 120°↓</b>                                      |
| <b>Colour</b>                     | <b>white</b>  |
| <b>U. G. R</b>                    | <b>&lt;19</b>   |
| <b>Chip Brand</b>                 | <b>Everlight</b>  |
| <b>Control gear included</b>      | <b>yes</b>  |
| <b>Control gear</b>               | <b>1-10V. Motion sensor and daylight sensor included.</b> |
| <b>Power Factor</b>               | <b>&gt;0,95</b>   |
| <b>Flicker Free</b>               | <b>yes</b>  |
| <b>Average life time (h)</b>      | <b>L80 B20, 50,000hrs</b>                                 |
| <b>Colour temperature (K)</b>     | <b>3000K</b>  |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>  |
| <b>CRI</b>                        | <b>80</b>   |

#### Dimensions

**Product dimensions (mm)** 696\*300\*1351mm

#### Scheme

