



| Dimensions | |
|---|---|
| **Product dimensions (mm)** | **696*300*1351mm** |

**Scheme**




## WORKSTATION TABLE

Lavov architectural luminaire from the family WORKSTATION TABLE with a power of 70.0 (35,0↑ / 35,0↓)W and an optics 120º↑ / 120º↓ degrees beam angle with UGR19. CCT 4000K. With a total lumen output of 4200lm↑ / 4200lm↓lm and an efficacy of 120lm/W . Made in Aluminium housing and pole and PC diffuser and finished in black color. Driver 1-10V. Motion sensor and daylight sensor included.

| | |
|---|---|
| **Item code** | **86.A009.2492.02** |
| **Product type** | **Indoor** |
| **Category** | **Architectural luminaires** |
| **Family** | **WORKSTATION** |
| **Subfamily** | **WORKSTATION TABLE** |
| **Pictograms** |  |



| Product | |
|---|---|
| **Real power (W)** | **70.0 (35,0↑ / 35,0↓)** |
| **Real luminous flux (Lm)** | **4200lm↑ / 4200lm↓** |
| **Luminous efficiency (Lm/W)** | **120** |
| **Beam angle (º)** | **120º↑ / 120º↓** |
| **Colour** | **black** |
| **U. G. R** | **19** |
| **Chip Brand** | **Everlight** |
| **Control gear included** | **yes** |
| **Control gear** | **1-10V. Motion sensor and daylight sensor included.** |
| **Power Factor** | **>0,96** |
| **Flicker Free** | **yes** |
| **Light source** | **LED** |
| **Type of LED** | **SMD** |
| **Average life time (h)** | **L80 B20, 50,000hrs** |
| **Colour temperature (K)** | **4000K** |
| **Colour consistency (SDCM)** | **SDCM4** |
| **CRI** | **80** |