



### STAR-S

Lavov surface downlight from the family STAR-S with a power of 30W and an optics of 45 degrees made in Die Cast Aluminum and Micro reflectors PC and louvers ABS with a real lumen output of 2250lm and an efficiency of 75lm/W, ON-OFF driver.

|                     |                           |
|---------------------|---------------------------|
| <b>Item code</b>    | <b>86.D032.3331.01</b>    |
| <b>Product type</b> | <b>Indoor</b>             |
| <b>Category</b>     | <b>Surface Downlights</b> |
| <b>Family</b>       | <b>STAR-S</b>             |

#### Pictograms



|                                   |                      |
|-----------------------------------|----------------------|
| <b>Product</b>                    |                      |
| <b>Real power (W)</b>             | <b>30</b>            |
| <b>Real luminous flux (Lm)</b>    | <b>2340</b>          |
| <b>Luminous efficiency (Lm/W)</b> | <b>78</b>            |
| <b>Beam angle (°)</b>             | <b>36</b>            |
| <b>Life time (h)</b>              | <b>50000h L80B10</b> |
| <b>IP</b>                         | <b>20</b>            |
| <b>Colour</b>                     | <b>White</b>         |
| <b>U. G. R</b>                    | <b>&lt;19</b>        |
| <b>Control gear included</b>      | <b>Yes</b>           |
| <b>Control gear</b>               | <b>ON-OFF</b>        |
| <b>Colour temperature (K)</b>     | <b>3000</b>          |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>     |
| <b>CRI</b>                        | <b>90</b>            |

### Dimensions

**Product dimensions (mm)**    **L403\*W33\*H60**

### Scheme



### Photometry

