



### GAP S2

Lavov downlight from the family GAP S2 with a power of 2x20W and a reflector of 36 degrees beam angle. With a total lumen output of 4000lm and an efficacy of 100lm/W. CCT 3000K. . Made in Die Cast Aluminum and finished in White color. DALI driver.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.D050.2333.01</b> |
|------------------|------------------------|

|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                   |
|-----------------|-------------------|
| <b>Category</b> | <b>Downlights</b> |
|-----------------|-------------------|

|               |            |
|---------------|------------|
| <b>Family</b> | <b>GAP</b> |
|---------------|------------|

|                  |               |
|------------------|---------------|
| <b>Subfamily</b> | <b>GAP S2</b> |
|------------------|---------------|

**Pictograms**

### Product

|                       |             |
|-----------------------|-------------|
| <b>Real power (W)</b> | <b>2x20</b> |
|-----------------------|-------------|

|                                |             |
|--------------------------------|-------------|
| <b>Real luminous flux (Lm)</b> | <b>4000</b> |
|--------------------------------|-------------|

|                                   |            |
|-----------------------------------|------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>100</b> |
|-----------------------------------|------------|

|                       |           |
|-----------------------|-----------|
| <b>Beam angle (°)</b> | <b>36</b> |
|-----------------------|-----------|

|                      |                       |
|----------------------|-----------------------|
| <b>Life time (h)</b> | <b>50000 h L80B10</b> |
|----------------------|-----------------------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>White</b> |
|---------------|--------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>Yes</b> |
|------------------------------|------------|

|                     |             |
|---------------------|-------------|
| <b>Control gear</b> | <b>DALI</b> |
|---------------------|-------------|

|                     |            |
|---------------------|------------|
| <b>Flicker Free</b> | <b>Yes</b> |
|---------------------|------------|

|                     |            |
|---------------------|------------|
| <b>Light source</b> | <b>LED</b> |
|---------------------|------------|

|                    |            |
|--------------------|------------|
| <b>Type of LED</b> | <b>COB</b> |
|--------------------|------------|

|                               |              |
|-------------------------------|--------------|
| <b>Colour temperature (K)</b> | <b>3000K</b> |
|-------------------------------|--------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>90</b> |
|------------|-----------|

### Scheme

