



MINI 4

Lavov downlight from the family MINI with a power of 3W, CRI 90 and CCT 2700K, 15 degrees beam angle. With a total lumen output of 134lm, and a luminous efficacy of 44.666666666667lm/W. Made in Die Cast Aluminum and finished in White color. ON/OFF driver.

| | |
|------------------|------------------------|
| Item code | 86.D070.2211.01 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-------------------|
| Category | Downlights |
|-----------------|-------------------|

| | |
|---------------|-------------|
| Family | MINI |
|---------------|-------------|

| | |
|------------------|---------------|
| Subfamily | MINI 4 |
|------------------|---------------|

| | |
|-------------------|---|
| Pictograms |      |
|-------------------|---|

CRI 90

CE

Driver INCL.

On Off

DALI

IP 20

Product

| | |
|-----------------------|----------|
| Real power (W) | 3 |
|-----------------------|----------|

| | |
|--------------------------------|------------|
| Real luminous flux (Lm) | 134 |
|--------------------------------|------------|

| | |
|-----------------------------------|------------------------|
| Luminous efficiency (Lm/W) | 44.666666666667 |
|-----------------------------------|------------------------|

| | |
|-----------------------|-----------|
| Beam angle (°) | 15 |
|-----------------------|-----------|

| | |
|----------------------|-----------------------|
| Life time (h) | 50000 h L80B10 |
|----------------------|-----------------------|

| | |
|-----------|-----------|
| IP | 20 |
|-----------|-----------|

| | |
|------------------------------------|-----------------|
| Electrical class insulation | Clas III |
|------------------------------------|-----------------|

| | |
|---------------|--------------|
| Colour | White |
|---------------|--------------|

| | |
|----------------|---------------|
| U. G. R | <19 |
|----------------|---------------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|---------------|
| Control gear | ON/OFF |
|---------------------|---------------|

| | |
|---------------------|------------|
| Flicker Free | Yes |
|---------------------|------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|------------|
| Type of LED | SMD |
|--------------------|------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 2700 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 90 |
|------------|-----------|

Dimensions

| | |
|--------------------------------|----------------|
| Product dimensions (mm) | Ø30*H68 |
|--------------------------------|----------------|

Scheme

