



### MINI F

Lavov downlight from the family MINI F with a power of 7W and a beam angle of 24°. Finished in White colour. Fixed version. With a total lumen output of 350lm and a luminous efficacy of 50lm/W. Made in Die Cast Aluminum. Driver DALI. CCT 2700K.

#### Dimensions

Product dimensions (mm) **Ø35\*H93.5mm**

#### Scheme



|              |                 |
|--------------|-----------------|
| Item code    | 86.D102.3223.01 |
| Product type | Indoor          |
| Category     | Downlights      |
| Family       | MINI            |
| Subfamily    | MINI F          |
| Pictograms   |                 |

#### Product

|                             |                |
|-----------------------------|----------------|
| Real power (W)              | 7              |
| Real luminous flux (Lm)     | 350            |
| Luminous efficiency (Lm/W)  | 50             |
| Beam angle (&ordm;)         | 24             |
| Life time (h)               | 50000 h L80B10 |
| IP                          | 20             |
| Electrical class insulation | Clas II        |
| Colour                      | White          |
| Control gear included       | Yes            |
| Control gear                | DALI           |
| Flicker Free                | Yes            |
| Light source                | LED            |
| Type of LED                 | COB            |
| Colour temperature (K)      | 2700           |
| Colour consistency (SDCM)   | SDCM<3         |
| CRI                         | 90             |