



### NEW PERFORM-RB Smart


Lavov downlight from the family PERFORM-RB with a power of 25W and a beam angle of 80°. Finished in White trim and gold reflector. Dimensions ø115\*H73mm. With a total lumen output of 2500lm and a luminous efficacy of 100lm/W. Made in Die Cast Aluminum. Driver DALI. CCT 4000K. UGR19.

#### Dimensions

Product dimensions (mm) ø115\*H71mm

#### Scheme

Cut out: 95mm



|              |                      |
|--------------|----------------------|
| Item code    | 86.D123.2449.D1      |
| Product type | Indoor               |
| Category     | Downlights           |
| Family       | NEW PERFORM          |
| Subfamily    | NEW PERFORM-RB Smart |
| Pictograms   |                      |

#### Product

|                             |                               |
|-----------------------------|-------------------------------|
| Real power (W)              | 25                            |
| Real luminous flux (Lm)     | 2500                          |
| Luminous efficiency (Lm/W)  | 100                           |
| Beam angle (°)              | 80                            |
| Life time (h)               | 50000 h L80B10                |
| IP                          | 20                            |
| Electrical class insulation | Clas II                       |
| Colour                      | White trim and gold reflector |
| U. G. R                     | <19                           |
| Control gear included       | Yes                           |
| Control gear                | DALI Casambi ready            |
| Flicker Free                | Yes                           |
| Light source                | LED                           |
| Type of LED                 | COB                           |
| Colour temperature (K)      | 4000                          |
| Colour consistency (SDCM)   | SDCM<3                        |
| CRI                         | 80                            |