



NEW PERFORM-RB Smart


Lavov downlight from the family PERFORM-RB with a power of 15W and a beam angle of 80° . Finished in White trim and gold reflector. Dimensions ø165*H98mm. With a total lumen output of 1500lm and a luminous efficacy of 100lm/W. Made in Die Cast Aluminum. Driver DALI. CCT 4000K. UGR19.

| Item code | 86.D123.4449.D1 Indoor Downlights | | |
|--------------|-----------------------------------|--|--|
| Product type | | | |
| Category | | | |
| Family | NEW PERFORM | | |
| Subfamily | NEW PERFORM-RB Smart | | |
| Pictograms | 220 v CRI C C Driver | | |
| | On | | |

| Dimensions | |
|-------------------------|-----------|
| Product dimensions (mm) | ø90*H60mm |

Scheme

Cut out:75mm



| Book of | | |
|-----------------------------|-------------------------------|--|
| Product | | |
| Real power (W) | 15 | |
| Real luminous flux (Lm) | 1500 | |
| Luminous efficiency (Lm/W) | 100 | |
| Beam angle (º) | 80 | |
| Life time (h) | 50000 h L80B10 | |
| IP | 20 | |
| Electrical class insulation | Clas II | |
| Colour | White trim and gold reflector | |
| U. G. R | <19 | |
| Control gear included | Yes | |
| Control gear | DALI Casambi ready | |
| Flicker Free | Yes | |
| Light source | LED | |
| Type of LED | SMD | |
| Colour temperature (K) | 4000 | |
| Colour consistency (SDCM) | SDCM<3 | |
| CRI | 80 | |