




NEW PERFORM-S


Lavov downlight from the family NEW PERFORM-S with a power of 25W and a beam angle of 36°. Finished in White trim and black reflector. Dimensions 115*115*H73mm. With a total lumen output of 2500lm and a luminous efficacy of 100lm/W. Made in Die Cast Aluminum. Driver DALI. CCT 3000K. UGR19.

| | |
|---------------------|---|
| Item code | 86.D125.2323.B1 |
| Product type | Indoor |
| Category | Downlights |
| Family | NEW PERFORM |
| Subfamily | NEW PERFORM-S |
| Pictograms |  |

Dimensions

Product dimensions (mm) **115*115*H73mm**

Scheme



| | |
|------------------------------------|---------------------------------------|
| Product | |
| Real power (W) | 25 |
| Real luminous flux (Lm) | 2500 |
| Luminous efficiency (Lm/W) | 100 |
| Beam angle (&ordm;) | 36 |
| Life time (h) | 50000 h L80B10 |
| IP | 20 |
| Electrical class insulation | Clas II |
| Colour | White trim and black reflector |
| U. G. R | <19 |
| Control gear included | Yes |
| Control gear | DALI |
| Flicker Free | Yes |
| Light source | LED |
| Type of LED | COB |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |