



NEW PERFORM-S


Lavov downlight from the family NEW PERFORM-S with a power of 25W and a beam angle of 60°. Finished in White trim and white reflector. Dimensions 115*115*H73mm. With a total lumen output of 2500lm and a luminous efficacy of 100lm/W. Made in Die Cast Aluminum. Driver DALI. CCT 4000K. UGR19.

Dimensions

Product dimensions (mm) **115*115*H73mm**

Scheme



| | |
|--------------|-------------------------------------------------------------------------------------|
| Item code | 86.D125.2433.A1 |
| Product type | Indoor |
| Category | Downlights |
| Family | NEW PERFORM |
| Subfamily | NEW PERFORM-S |
| Pictograms |  |

| | |
|-----------------------------|---------------------------------------|
| Product | |
| Real power (W) | 25 |
| Real luminous flux (Lm) | 2500 |
| Luminous efficiency (Lm/W) | 100 |
| Beam angle (°) | 60 |
| Life time (h) | 50000 h L80B10 |
| IP | 20 |
| Electrical class insulation | Clas II |
| Colour | White trim and white reflector |
| U. G. R | 19 |
| Control gear included | Yes |
| Control gear | DALI |
| Flicker Free | Yes |
| Light source | LED |
| Type of LED | COB |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM3 |
| CRI | 80 |