



Waterproof

Lavov downlight from the family Waterproof eco with a power of 50W and a 25 degrees beam angle. With a total lumen output of 4250lm and a luminous efficiency of 85lm/W. Driver ON-OFF .Made in die cast aluminium . Class II isolation. IP65 . Mains voltage 180-240V . UGR. Finished in White colour. CCT 3000K.CRI90. Dimensions ø215\*105mm cut size: ø200mm.

|              |                 |
|--------------|-----------------|
| Item code    | 86.D130.3321.01 |
| Product type | Indoor          |
| Category     | Downlights      |
| Family       | Waterproof      |
| Subfamily    | Waterproof      |
| Pictograms   |                 |

|                             |          |
|-----------------------------|----------|
| Product                     |          |
| Real power (W)              | 50       |
| Real luminous flux (Lm)     | 4250     |
| Luminous efficiency (Lm/W)  | 85       |
| Beam angle (°)              | 25       |
| IP                          | 65.0     |
| Electrical class insulation | Class II |
| Electrical feeding          | 180-240V |
| Colour                      | White    |
| Control gear included       | Yes      |
| Control gear                | ON-OFF   |
| Flicker Free                | Yes      |
| Light source                | LED      |
| Type of LED                 | COB      |
| Colour temperature (K)      | 3000     |
| Colour consistency (SDCM)   | SDCM5    |
| CRI                         | 90       |

|                         |                             |
|-------------------------|-----------------------------|
| Dimensions              |                             |
| Product dimensions (mm) | ø215*105mm cut size: ø200mm |
| Scheme                  |                             |

