



Waterproof

Lavov downlight from the family Waterproof eco with a power of 50W and a 55 degrees beam angle. With a total lumen output of 4250lm and a luminous efficiency of 85lm/W. Driver DALI .Made in die cast aluminium . Class II insulation. IP65 . Mains voltage 180-240V . UGR. Finished in White colour. CCT 3000K.CRI90. Dimensions $\varnothing 215 \times 105\text{mm}$ cut size: $\varnothing 200\text{mm}$.

Item code	86.D130.3343.01
Product type	Indoor
Category	Downlights
Family	Waterproof
Subfamily	Waterproof
Pictograms	220 240 V CRI 80 SDCM 3 Driver INCL. On Off 50000h L80B10 IP 65

Product	
Real power (W)	50
Real luminous flux (Lm)	4250
Luminous efficiency (Lm/W)	85
Beam angle (°)	55
IP	65.0
Electrical class insulation	Class II
Electrical feeding	180-240V
Colour	White
Control gear included	Yes
Control gear	DALI
Flicker Free	Yes
Light source	LED
Type of LED	COB
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM5
CRI	90

Dimensions

Product dimensions (mm) $\varnothing 215 \times 105\text{mm}$ cut size: $\varnothing 200\text{mm}$

Scheme

