Dimensions

Scheme

Product dimensions (mm)





| D. | ГΤ | R | 2 |
|----|----|---|---|

Lavov downlight from the family PTT R2 with a power of 2x18Wand a beam angle of 36° . Finished in Black colour. Trim version. With a total lumen output of 3600lm and a luminous efficacy of 100lm/W. Made in Die Cast Aluminum. Driver ON/OFF. CCT 3000K.

| Item code | 86.D147.3331.02 Indoor Downlights PTT | | | | |
|--------------|--|---------------------------------|-----------|-----------------------------------|-----------------|
| Product type | | | | | |
| Category | | | | | |
| Family | | | | | |
| Subfamily | PTT R2 | | | | |
| Pictograms | | ²²⁰ ₂₄₀ v | CRI 90 | C€ | Driver INCL. |
| | On Off | DALI | IP 20 | 50000h L 80 B 10 | ⊋ 355° |
| | 90° | | | | |

| Item code | 86.D147.3331.02 | | |
|--------------|----------------------------|--|--|
| Product type | Indoor | | |
| Category | Downlights | | |
| Family | РТТ | | |
| Subfamily | PTT R2 | | |
| Pictograms | 220 v CRI C C Driver INCL. | | |
| | On Off 20 1P 50000h 355 | | |
| | 90° | | |

| W194*105mm |
|------------------|
| H116mm |
| |
| Cut out:171*91mm |

Ø194x105xH105mm

| Product | - | |
|----------------------------|----------------|--|
| Real power (W) | 2x18 | |
| Real luminous flux (Lm) | 3600 | |
| Luminous efficiency (Lm/W) | 100 | |
| Beam angle (º) | 36 | |
| Life time (h) | 50000 h L80B10 | |
| Colour | Black | |
| Control gear included | Yes | |
| Control gear | ON/OFF | |
| Flicker Free | Yes | |
| Light source | LED | |
| Type of LED | СОВ | |
| Colour temperature (K) | 3000 | |
| Colour consistency (SDCM) | SDCM<3 | |
| CRI | 90 | |