



### PTT RT2 Smart

Lavov downlight from the family PTT RT2 Smart with a power of 2x18W and a beam angle of 24°. Finished in Black colour. Trimless version. With a total lumen output of 3600lm and a luminous efficacy of 100lm/W. Made in Die Cast Aluminum. Driver Dimmable Casamby ready. CCT 4000K.

|                     |                        |
|---------------------|------------------------|
| <b>Item code</b>    | <b>86.D149.3429.02</b> |
| <b>Product type</b> | <b>Indoor</b>          |
| <b>Category</b>     | <b>Downlights</b>      |
| <b>Family</b>       | <b>PTT</b>             |
| <b>Subfamily</b>    | <b>PTT RT2 Smart</b>   |
| <b>Pictograms</b>   |                        |

### Dimensions

**Product dimensions (mm)**      **Ø194x105xH105mm**

### Scheme



|                                   |                               |
|-----------------------------------|-------------------------------|
| <b>Product</b>                    |                               |
| <b>Real power (W)</b>             | <b>2x18</b>                   |
| <b>Real luminous flux (Lm)</b>    | <b>3600</b>                   |
| <b>Luminous efficiency (Lm/W)</b> | <b>100</b>                    |
| <b>Beam angle (&amp;ordm;)</b>    | <b>24</b>                     |
| <b>Life time (h)</b>              | <b>50000 h L80B10</b>         |
| <b>Colour</b>                     | <b>Black</b>                  |
| <b>Control gear included</b>      | <b>Yes</b>                    |
| <b>Control gear</b>               | <b>Dimmable Casamby ready</b> |
| <b>Flicker Free</b>               | <b>Yes</b>                    |
| <b>Light source</b>               | <b>LED</b>                    |
| <b>Type of LED</b>                | <b>COB</b>                    |
| <b>Colour temperature (K)</b>     | <b>4000</b>                   |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>              |
| <b>CRI</b>                        | <b>90</b>                     |