



PRO-DR Smart

Lavov downlight from the family PRO-DR Smart with a power of 17,73W and an optics 12 degrees . CCT 3000K. With a total lumen output of 1556lm and a luminous efficiency of 87,76lm/W.DALI+wireless Casambi driver. Made in die cast aluminum and finished in grey color.

| | |
|------------------|------------------------|
| Item code | 86.DS25.2319.03 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-------------------|
| Category | Downlights |
|-----------------|-------------------|


| | |
|---------------|--------------|
| Family | PRO-D |
|---------------|--------------|

| | |
|------------------|---------------------|
| Subfamily | PRO-DR Smart |
|------------------|---------------------|

| | |
|-------------------|---|
| Pictograms |      |
| |      |



Scheme



Product

| | |
|-----------------------|--------------|
| Real power (W) | 17.73 |
|-----------------------|--------------|

| | |
|--------------------------------|-------------|
| Real luminous flux (Lm) | 1556 |
|--------------------------------|-------------|

| | |
|-----------------------------------|--------------|
| Luminous efficiency (Lm/W) | 87.76 |
|-----------------------------------|--------------|

| | |
|-----------------------|-----------|
| Beam angle (°) | 12 |
|-----------------------|-----------|

| | |
|----------------------|-----------------------|
| Life time (h) | 50000 h L80B10 |
|----------------------|-----------------------|

| | |
|-----------|-----------|
| IP | 20 |
|-----------|-----------|

| | |
|------------------------------------|----------------|
| Electrical class insulation | Clas II |
|------------------------------------|----------------|

| | |
|---------------|-------------|
| Colour | grey |
|---------------|-------------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|------------------------------|
| Control gear | DALI+wireless Casambi |
|---------------------|------------------------------|

| | |
|---------------------|------------|
| Flicker Free | Yes |
|---------------------|------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|------------|
| Type of LED | COB |
|--------------------|------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 80 |
|------------|-----------|