



STAR Smart

Lavov downlight from the family STAR with a power of 10W and an optics 15 degrees . CCT 4000K. With a total lumen output of 700lm and a luminous efficiency of 70lm/W.DALI+wireless Casambi driver. Made in die cast aluminum and finished in White color. UGR

| | |
|------------------|------------------------|
| Item code | 86.DS29.3419.01 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-------------------|
| Category | Downlights |
|-----------------|-------------------|

| | |
|---------------|-------------|
| Family | STAR |
|---------------|-------------|

| | |
|------------------|-------------------|
| Subfamily | STAR Smart |
|------------------|-------------------|

| | |
|-------------------|---|
| Pictograms |      |
| |     |



Product

| | |
|-----------------------|-----------|
| Real power (W) | 10 |
|-----------------------|-----------|

| | |
|--------------------------------|------------|
| Real luminous flux (Lm) | 700 |
|--------------------------------|------------|

| | |
|-----------------------------------|-----------|
| Luminous efficiency (Lm/W) | 70 |
|-----------------------------------|-----------|

| | |
|-----------------------|-----------|
| Beam angle (°) | 15 |
|-----------------------|-----------|

| | |
|----------------------|-----------------------|
| Life time (h) | 50000 h L80B10 |
|----------------------|-----------------------|

| | |
|-----------|-----------|
| IP | 20 |
|-----------|-----------|

| | |
|------------------------------------|----------------|
| Electrical class insulation | Clas II |
|------------------------------------|----------------|

| | |
|---------------|--------------|
| Colour | White |
|---------------|--------------|

| | |
|----------------|------------------|
| U. G. R | UGR<19 |
|----------------|------------------|

| | |
|---------------------|------------------------------|
| Control gear | DALI+wireless Casambi |
|---------------------|------------------------------|

| | |
|---------------------|------------|
| Flicker Free | Yes |
|---------------------|------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|------------|
| Type of LED | SMD |
|--------------------|------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 4000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 80 |
|------------|-----------|

Scheme

