



### ZENITH IP65S Smart

Lavov downlight from the family ZENITH IP65S Smart with a power of 20W and a 12 degrees beam angle. CCT 3000K. White color. With a total lumen output of 1600lm and a luminous efficacy of 80lm/W. Made in Die Cast Aluminum. IP65degree of protection. Class II isolation. DALI wireless Casambi driver. UGR19. CRI90.

#### Dimensions

Product dimensions (mm) **85\*85\*121mm**

#### Scheme



|              |                           |
|--------------|---------------------------|
| Item code    | <b>86.DS85.1319.01</b>    |
| Product type | <b>Indoor</b>             |
| Category     | <b>Downlights</b>         |
| Family       | <b>ZENITH</b>             |
| Subfamily    | <b>ZENITH IP65S Smart</b> |
| Pictograms   |                           |

|                             |                              |
|-----------------------------|------------------------------|
| <b>Product</b>              |                              |
| Real power (W)              | <b>20</b>                    |
| Real luminous flux (Lm)     | <b>1600</b>                  |
| Luminous efficiency (Lm/W)  | <b>80</b>                    |
| Beam angle (°)              | <b>12</b>                    |
| Life time (h)               | <b>50000 h L80B10</b>        |
| IP                          | <b>65</b>                    |
| Electrical class insulation | <b>Clas II</b>               |
| Colour                      | <b>White</b>                 |
| U. G. R                     | <b>19</b>                    |
| Control gear                | <b>DALI wireless Casambi</b> |
| Flicker Free                | <b>Yes</b>                   |
| Light source                | <b>LED</b>                   |
| Type of LED                 | <b>COB</b>                   |
| Colour temperature (K)      | <b>3000</b>                  |
| Colour consistency (SDCM)   | <b>SDCM3</b>                 |
| CRI                         | <b>80</b>                    |