



ZENITH IP65S Smart


Lavov downlight from the family ZENITH IP65S Smart with a power of 30W and a 24 degrees beam angle. CCT 4000K. black color. With a total lumen output of 2400lm and a luminous efficacy of 80lm/W. Made in Die Cast Aluminum. IP65degree of protection. Class II isolation. DALI wireless Casambi driver. UGR19. CRI90.

Dimensions

Product dimensions (mm) 105*105*146mm

Scheme



| | |
|--------------|--|
| Item code | 86.DS85.2429.02 |
| Product type | Indoor |
| Category | Downlights |
| Family | ZENITH |
| Subfamily | ZENITH IP65S Smart |
| Pictograms |  |

| | |
|-----------------------------|-----------------------|
| Product | |
| Real power (W) | 30 |
| Real luminous flux (Lm) | 2400 |
| Luminous efficiency (Lm/W) | 80 |
| Beam angle (º) | 24 |
| Life time (h) | 50000 h L80B10 |
| IP | 65 |
| Electrical class insulation | Clas II |
| Colour | black |
| U. G. R | 19 |
| Control gear | DALI wireless Casambi |
| Flicker Free | Yes |
| Light source | LED |
| Type of LED | COB |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |