



FLEX C

Lavov tracklight from the family FLEX C with a power of 5W and an optics 36° degrees beam angle . CCT 4000K. With a total lumen output of 325lm and an efficacy of 65lm/W . Made in Die Cast Aluminum body and PC adapter and finished in Black color. ON-OFF driver.

| | |
|------------------|------------------------|
| Item code | 86.FT01.1431.02 |
|------------------|------------------------|

| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|--------------------|
| Category | Tracklights |
|-----------------|--------------------|

| | |
|---------------|-------------|
| Family | FLEX |
|---------------|-------------|

| | |
|------------------|---------------|
| Subfamily | FLEX C |
|------------------|---------------|

| | |
|-------------------|---|
| Pictograms |      |
|-------------------|---|

XX°

CRI
90

CE

Driver
INCL.On
Off


DALI

IP
20

Dimensions

Product dimensions (mm) 197* ϕ 30*127mm

Scheme



Product

| | |
|-----------------------|----------|
| Real power (W) | 5 |
|-----------------------|----------|

| | |
|--------------------------------|------------|
| Real luminous flux (Lm) | 325 |
|--------------------------------|------------|

| | |
|-----------------------------------|-----------|
| Luminous efficiency (Lm/W) | 65 |
|-----------------------------------|-----------|

| | |
|-----------------------|------------|
| Beam angle (°) | 36° |
|-----------------------|------------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L80B10 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 20 |
|-----------|-----------|

| | |
|------------------------------------|------------------|
| Electrical class insulation | Class III |
|------------------------------------|------------------|

| | |
|---------------|--------------|
| Colour | Black |
|---------------|--------------|

| | |
|------------------------------|------------|
| Control gear included | yes |
|------------------------------|------------|

| | |
|---------------------|---------------|
| Control gear | ON-OFF |
|---------------------|---------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 4000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 90 |
|------------|-----------|