



### FLEX C

Lavov tracklight from the family FLEX C with a power of 5W and an optics 36° degrees beam angle . CCT 4000K. With a total lumen output of 325lm and an efficacy of 65lm/W . Made in Die Cast Aluminum body and PC adapter and finished in Black color. ON-OFF driver.

<b>Item code</b>	<b>86.FT01.1431.02</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Tracklights</b>
-----------------	--------------------

<b>Family</b>	<b>FLEX</b>
---------------	-------------

<b>Subfamily</b>	<b>FLEX C</b>
------------------	---------------

<b>Pictograms</b>	    
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

XX°

CRI  
90

CE

Driver  
INCL.On  
Off


DALI

IP  
20

### Dimensions

**Product dimensions (mm)** 197\* $\phi$ 30\*127mm

### Scheme



### Product

<b>Real power (W)</b>	<b>5</b>
-----------------------	----------

<b>Real luminous flux (Lm)</b>	<b>325</b>
--------------------------------	------------

<b>Luminous efficiency (Lm/W)</b>	<b>65</b>
-----------------------------------	-----------

<b>Beam angle (°)</b>	<b>36°</b>
-----------------------	------------

<b>Life time (h)</b>	<b>50000h L80B10</b>
----------------------	----------------------

<b>IP</b>	<b>20</b>
-----------	-----------

<b>Electrical class insulation</b>	<b>Class III</b>
------------------------------------	------------------

<b>Colour</b>	<b>Black</b>
---------------	--------------

<b>Control gear included</b>	<b>yes</b>
------------------------------	------------

<b>Control gear</b>	<b>ON-OFF</b>
---------------------	---------------

<b>Colour temperature (K)</b>	<b>4000</b>
-------------------------------	-------------

<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
----------------------------------	------------------

<b>CRI</b>	<b>90</b>
------------	-----------