



### FLEX LF

Lavov tracklight from the family FLEX LF with a power of 18W and an optics 110° degrees beam angle . CCT 4000K. With a total lumen output of 1440lm and an efficacy of 80lm/W . Made in Die Cast Aluminum body and PC adapter and finished in Black color. ON-OFF driver.

<b>Item code</b>	<b>86.FT04.2401.02</b>
------------------	------------------------

<b>Product type</b>	<b>Indoor</b>
---------------------	---------------

<b>Category</b>	<b>Tracklights</b>
-----------------	--------------------

<b>Family</b>	<b>FLEX</b>
---------------	-------------

<b>Subfamily</b>	<b>FLEX LF</b>
------------------	----------------

<b>Pictograms</b>	    
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

XX° CRI 90 CE Driver INCL. On Off

 IP 20

### Dimensions

<b>Product dimensions (mm)</b>	<b>472*27.5*45mm</b>
--------------------------------	----------------------

### Product

<b>Real power (W)</b>	<b>18</b>
-----------------------	-----------

<b>Real luminous flux (Lm)</b>	<b>1440</b>
--------------------------------	-------------

<b>Luminous efficiency (Lm/W)</b>	<b>80</b>
-----------------------------------	-----------

<b>Beam angle (°)</b>	<b>110°</b>
-----------------------	-------------

<b>Life time (h)</b>	<b>50000h L80B10</b>
----------------------	----------------------

<b>IP</b>	<b>20</b>
-----------	-----------

<b>Electrical class insulation</b>	<b>Class III</b>
------------------------------------	------------------

<b>Colour</b>	<b>Black</b>
---------------	--------------

<b>Control gear included</b>	<b>yes</b>
------------------------------	------------

<b>Control gear</b>	<b>ON-OFF</b>
---------------------	---------------

<b>Colour temperature (K)</b>	<b>4000</b>
-------------------------------	-------------

<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
----------------------------------	------------------

<b>CRI</b>	<b>90</b>
------------	-----------