



### FLEX SCD1

Lavov decorative tracklight from the family FLEX SCD1 with a power of 12W and an optics 60° degrees beam angle . CCT 3000K. With a total lumen output of 780lm and an efficacy of 65lm/W . Made in Die Cast Aluminum body and PC adapter and finished in Black color. ON-OFF driver.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.FT14.1331.02</b> |
|------------------|------------------------|

|                     |               |
|---------------------|---------------|
| <b>Product type</b> | <b>Indoor</b> |
|---------------------|---------------|

|                 |                    |
|-----------------|--------------------|
| <b>Category</b> | <b>Tracklights</b> |
|-----------------|--------------------|

|               |             |
|---------------|-------------|
| <b>Family</b> | <b>FLEX</b> |
|---------------|-------------|

|                  |                  |
|------------------|------------------|
| <b>Subfamily</b> | <b>FLEX SCD1</b> |
|------------------|------------------|

|                   |   |
|-------------------|---|
| <b>Pictograms</b> |      |
|                   |      |

### Dimensions

**Product dimensions (mm)** 197\*φ157\*1200mm

### Product

|                       |           |
|-----------------------|-----------|
| <b>Real power (W)</b> | <b>12</b> |
|-----------------------|-----------|

|                                |            |
|--------------------------------|------------|
| <b>Real luminous flux (Lm)</b> | <b>780</b> |
|--------------------------------|------------|

|                                   |           |
|-----------------------------------|-----------|
| <b>Luminous efficiency (Lm/W)</b> | <b>65</b> |
|-----------------------------------|-----------|

|                       |            |
|-----------------------|------------|
| <b>Beam angle (°)</b> | <b>60°</b> |
|-----------------------|------------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>50000h L80B10</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>20</b> |
|-----------|-----------|

|                                    |                  |
|------------------------------------|------------------|
| <b>Electrical class insulation</b> | <b>Class III</b> |
|------------------------------------|------------------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>Black</b> |
|---------------|--------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>yes</b> |
|------------------------------|------------|

|                     |               |
|---------------------|---------------|
| <b>Control gear</b> | <b>ON-OFF</b> |
|---------------------|---------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>3000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>90</b> |
|------------|-----------|