



### LYRA II

Lavov flood light from the family LYRA II with a power of 150W and an optics 110 degrees . CCT 4000K. With a total lumen output of 18000lm and a luminous efficiency of 120lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 07 degree of protection.


|                  |                         |
|------------------|-------------------------|
| <b>Item code</b> | <b>86.10017.7441.02</b> |
|------------------|-------------------------|

|                     |                |
|---------------------|----------------|
| <b>Product type</b> | <b>Outdoor</b> |
|---------------------|----------------|


|                 |                    |
|-----------------|--------------------|
| <b>Category</b> | <b>Floodlights</b> |
|-----------------|--------------------|

|               |                |
|---------------|----------------|
| <b>Family</b> | <b>LYRA II</b> |
|---------------|----------------|

**Pictograms**



### Scheme



### Product

|                       |            |
|-----------------------|------------|
| <b>Real power (W)</b> | <b>150</b> |
|-----------------------|------------|

|                                |              |
|--------------------------------|--------------|
| <b>Real luminous flux (Lm)</b> | <b>18000</b> |
|--------------------------------|--------------|

|                                   |            |
|-----------------------------------|------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>120</b> |
|-----------------------------------|------------|

|                       |            |
|-----------------------|------------|
| <b>Beam angle (°)</b> | <b>110</b> |
|-----------------------|------------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>36000h L70B50</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>66</b> |
|-----------|-----------|

|                                    |                |
|------------------------------------|----------------|
| <b>Electrical class insulation</b> | <b>Class I</b> |
|------------------------------------|----------------|

|               |              |
|---------------|--------------|
| <b>Colour</b> | <b>Black</b> |
|---------------|--------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>Yes</b> |
|------------------------------|------------|

|                     |               |
|---------------------|---------------|
| <b>Control gear</b> | <b>ON-OFF</b> |
|---------------------|---------------|

|                     |            |
|---------------------|------------|
| <b>Light source</b> | <b>LED</b> |
|---------------------|------------|

|                    |             |
|--------------------|-------------|
| <b>Type of LED</b> | <b>2835</b> |
|--------------------|-------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>4000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;5</b> |
|----------------------------------|------------------|

|            |            |
|------------|------------|
| <b>CRI</b> | <b>≥80</b> |
|------------|------------|

|           |           |
|-----------|-----------|
| <b>IK</b> | <b>07</b> |
|-----------|-----------|