




AQUILA II

Lavov flood light from the family AQUILA II with a power of 50W and an optics 60° degrees . CCT 4000K. With a total lumen output of 7500lm and a luminous efficiency of 150lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

|              |  |
|--------------|--|
| Item code    | 86.I0018.1421.02   |
| Product type | Outdoor  |
| Category     | Floodlights  |
| Family       | AQUILA II  |
| Pictograms   | <div><div></div><div>50<br/>60 Hz</div><div>220<br/>240 V</div><div><br/>850°</div><div>SDCM<br/>3</div></div> <div><div>CE</div><div>Driver<br/>INCL.</div><div>On<br/>Off</div><div></div><div></div></div> <div><div>IP<br/>66</div><div>CRI<br/>70</div><div>IK<br/>08</div><div>50000h<br/>L70B50</div></div> |

Scheme



|                             |               |
|-----------------------------|---------------|
| Product                     |               |
| Real power (W)              | 50            |
| Real luminous flux (Lm)     | 7500          |
| Luminous efficiency (Lm/W)  | 150           |
| Beam angle (°)              | 60°           |
| Life time (h)               | 50000h L70B50 |
| IP                          | 66            |
| Electrical class insulation | Class I       |
| Colour                      | Black         |
| Control gear included       | Yes           |
| Control gear                | ON-OFF        |
| Light source                | LED           |
| Type of LED                 | 2835          |
| Colour temperature (K)      | 4000          |
| Colour consistency (SDCM)   | SDCM<5        |
| CRI                         | ≥70           |
| IK                          | 08            |