




AQUILA II

Lavov flood light from the family AQUILA II with a power of 50W and an optics 26x60° tilt10° degrees . CCT 4000K. With a total lumen output of 7500lm and a luminous efficiency of 150lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

Item code	86.I0018.1461.02
Product type	Outdoor
Category	Floodlights
Family	AQUILA II
Pictograms	<div><div></div><div>50 60 Hz</div><div>220 240 V</div><div></div><div>850°</div><div>SDCM 3</div></div> <div><div>CE</div><div>Driver INCL.</div><div>On Off</div><div></div><div></div></div> <div><div>IP 66</div><div>CRI 70</div><div>IK 08</div><div>50000h L70B50</div></div>

Scheme



Product	
Real power (W)	50
Real luminous flux (Lm)	7500
Luminous efficiency (Lm/W)	150
Beam angle (°)	26x60° tilt10°
Life time (h)	50000h L70B50
IP	66
Electrical class insulation	Class I
Colour	Black
Control gear included	Yes
Control gear	ON-OFF
Light source	LED
Type of LED	2835
Colour temperature (K)	4000
Colour consistency (SDCM)	SDCM<5
CRI	≥70
IK	08