

## **AQUILA II**

Lavov flood light from the family AQUILA II with a power of 100W and an optics 25° degrees . CCT 4000K. With a total lumen output of 15500lm and a luminous efficiency of 155lm/W.DALI driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

| Item code    | 86. 10018.2413.02                   |
|--------------|-------------------------------------|
| Product type | Indoor                              |
| Category     | Floodlights                         |
| Family       | AQUILA II                           |
| Subfamily    | AQUILA II                           |
| Pictograms   | 50 Hz 220 V 50° SDCM 3              |
|              | CE Driver INCL.                     |
|              | IP CRI IK 50000h<br>66 70 08 L70B50 |

| Product                     |               |
|-----------------------------|---------------|
| Real power (W)              | 100           |
| Real luminous flux (Lm)     | 15500         |
| Luminous efficiency (Lm/W)  | 155           |
| Beam angle (º)              | 25º           |
| Life time (h)               | 50000h L70B50 |
| IP                          | 66            |
| Electrical class insulation | Class I       |
| Colour                      | Black         |
| Control gear included       | Yes           |
| Control gear                | DALI          |
| Light source                | LED           |
| Type of LED                 | 2835          |
| Colour temperature (K)      | 4000          |
| Colour consistency (SDCM)   | SDCM<5        |
| CRI                         | ≥70           |
| IK                          | 08            |

