



### AQUILA II

Lavov flood light from the family AQUILA II with a power of 100W and an optics 25° degrees . CCT 4000K. With a total lumen output of 15500lm and a luminous efficiency of 155lm/W.DALI driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

### Scheme



<b>Item code</b>	<b>86.I0018.2413.02</b>
<b>Product type</b>	<b>Indoor</b>
<b>Category</b>	<b>Industrial</b>
<b>Family</b>	<b>AQUILA II</b>
<b>Subfamily</b>	<b>AQUILA II</b>
<b>Pictograms</b>	

<b>Product</b>	
<b>Real power (W)</b>	<b>100</b>
<b>Real luminous flux (Lm)</b>	<b>15500</b>
<b>Luminous efficiency (Lm/W)</b>	<b>155</b>
<b>Beam angle (°)</b>	<b>25°</b>
<b>Life time (h)</b>	<b>50000h L70B50</b>
<b>IP</b>	<b>66</b>
<b>Electrical class insulation</b>	<b>Class I</b>
<b>Colour</b>	<b>Black</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>DALI</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>2835</b>
<b>Colour temperature (K)</b>	<b>4000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM5</b>
<b>CRI</b>	<b>≥70</b>
<b>IK</b>	<b>08</b>