

AQUILA II

Lavov flood light from the family AQUILA II with a power of 100W and an optics 60º degrees . CCT 4000K. With a total lumen output of 15500lm and a luminous efficiency of 155lm/W.DALI driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

Item code 86. I0018.2423.02 Product type Outdoor Category Floodlights Family AQUILA II Subfamily AQUILA II Pictograms C∈ Driver IP CRI IK 50000h		
Category Floodlights Family AQUILA II Subfamily AQUILA II Pictograms	em code	86. 10018.2423.02
Family AQUILA II Subfamily Pictograms	roduct type	Outdoor
Subfamily Pictograms Subfamily AQUILA II Solution 10 to	ategory	Floodlights
Pictograms	amily	AQUILA II
CE Driver INCL	ubfamily	AQUILA II
CE INCL.	Pictograms	50 Hz 220 V > SDCM 3
IP CRI IK 50000h		
66 70 08 L70 B 50		

Product	
Real power (W)	100
Real luminous flux (Lm)	15500
Luminous efficiency (Lm/W)	155
Beam angle (º)	60º
Life time (h)	50000h L70B50
IP	66
Electrical class insulation	Class I
Colour	Black
Control gear included	Yes
Control gear	DALI
Light source	LED
Type of LED	2835
Colour temperature (K)	4000
Colour consistency (SDCM)	SDCM<5
CRI	≥70
IK	08

