

## AQUILA II

Lavov flood light from the family AQUILA II with a power of 100W and an optics 26x60° tilt10° degrees . CCT 4000K. With a total lumen output of 15500Im and a luminous efficiency of 155Im/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

| ltem code    | 86. 10018.2461.02                            |
|--------------|--|
| Product type | Outdoor                                      |
| Category     | Floodlights                                  |
| Family       | AQUILA II                                    |
| Subfamily    | AQUILA II                                    |
| Pictograms   | (→ 50 Hz 220 V )→ SDCM<br>60 Hz 240 V 350° 3 |
|              | CE Driver On Off                             |
|              | IP CRI IK 50000h<br>66 70 08 L70B50          |

| Product                     |                |
|-----------------------------|----------------|
| Real power (W)              | 100            |
| Real luminous flux (Lm)     | 15500          |
| Luminous efficiency (Lm/W)  | 155            |
| Beam angle (º)              | 26x60° tilt10° |
| Life time (h)               | 50000h L70B50  |
| IP                          | 66             |
| Electrical class insulation | Class I        |
| Colour                      | Black          |
| Control gear included       | Yes            |
| Control gear                | ON-OFF         |
| Light source                | LED            |
| Type of LED                 | 2835           |
| Colour temperature (K)      | 4000           |
| Colour consistency (SDCM)   | SDCM<5         |
| CRI                         | ≥70            |
| IK                          | 08             |

