



AQUILA II

Lavov flood light from the family AQUILA II with a power of 150W and an optics 60° degrees . CCT 4000K. With a total lumen output of 23250lm and a luminous efficiency of 155lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

| | |
|------------------|-------------------------|
| Item code | 86.10018.3421.02 |
|------------------|-------------------------|


| | |
|---------------------|---------------|
| Product type | Indoor |
|---------------------|---------------|

| | |
|-----------------|-------------------|
| Category | Industrial |
|-----------------|-------------------|


| | |
|---------------|------------------|
| Family | AQUILA II |
|---------------|------------------|

| | |
|------------------|------------------|
| Subfamily | AQUILA II |
|------------------|------------------|

| | |
|-------------------|---|
| Pictograms |      |
| |      |
| |     |



Scheme



Product

| | |
|-----------------------|------------|
| Real power (W) | 150 |
|-----------------------|------------|

| | |
|--------------------------------|--------------|
| Real luminous flux (Lm) | 23250 |
|--------------------------------|--------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 155 |
|-----------------------------------|------------|

| | |
|-----------------------|------------|
| Beam angle (°) | 60° |
|-----------------------|------------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L70B50 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 66 |
|-----------|-----------|

| | |
|------------------------------------|----------------|
| Electrical class insulation | Class I |
|------------------------------------|----------------|

| | |
|---------------|--------------|
| Colour | Black |
|---------------|--------------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|---------------|
| Control gear | ON-OFF |
|---------------------|---------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|-------------|
| Type of LED | 2835 |
|--------------------|-------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 4000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<5 |
|----------------------------------|------------------|

| | |
|------------|------------|
| CRI | ≥70 |
|------------|------------|

| | |
|-----------|-----------|
| IK | 08 |
|-----------|-----------|