FLOODLIGHTS - AQUILA II





AQUILA II

Lavov flood light from the family AQUILA II with a power of 150W and an optics 60^o degrees . CCT 4000K. With a total lumen output of 23250lm and a luminous efficiency of 155lm/W.DALI driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

| ltem code | 86.10018.3423.02 |
|--------------|---|
| Product type | Outdoor |
| Category | Floodlights |
| Family | AQUILA II |
| Subfamily | AQUILA II |
| Pictograms | (→) 50 Hz 220 V (→) 50 Hz 220 V 30 SDCM 3 |
| | |
| | IP CRI IK 50000h 66 70 08 L70B50 |

| Product | |
|-----------------------------|---------------|
| Real power (W) | 150 |
| Real luminous flux (Lm) | 23250 |
| Luminous efficiency (Lm/W) | 155 |
| Beam angle (º) | 60º |
| Life time (h) | 50000h L70B50 |
| IP | 66 |
| Electrical class insulation | Class I |
| Colour | Black |
| Control gear included | Yes |
| Control gear | DALI |
| Light source | LED |
| Type of LED | 2835 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<5 |
| CRI | ≥70 |
| IK | 08 |

Scheme



