



AQUILA II

Lavov flood light from the family AQUILA II with a power of 150W and an optics 26x60° tilt10° degrees . CCT 4000K. With a total lumen output of 23250lm and a luminous efficiency of 155lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

Item code	86.10018.3461.02
------------------	-------------------------

Product type	Indoor
---------------------	---------------

Category	Industrial
-----------------	-------------------


Family	AQUILA II
---------------	------------------

Subfamily	AQUILA II
------------------	------------------

Pictograms	    
	    
	   



Scheme



Product

Real power (W)	150
-----------------------	------------

Real luminous flux (Lm)	23250
--------------------------------	--------------

Luminous efficiency (Lm/W)	155
-----------------------------------	------------

Beam angle (°)	26x60° tilt10°
-----------------------	-----------------------

Life time (h)	50000h L70B50
----------------------	----------------------

IP	66
-----------	-----------

Electrical class insulation	Class I
------------------------------------	----------------

Colour	Black
---------------	--------------

Control gear included	Yes
------------------------------	------------

Control gear	ON-OFF
---------------------	---------------

Light source	LED
---------------------	------------

Type of LED	2835
--------------------	-------------

Colour temperature (K)	4000
-------------------------------	-------------

Colour consistency (SDCM)	SDCM<5
----------------------------------	------------------

CRI	≥70
------------	------------

IK	08
-----------	-----------