FLOODLIGHTS - AQUILA II





AQUILA II

Lavov flood light from the family AQUILA II with a power of 200W and an optics 55x125°, tilt55 degrees . CCT 4000K. With a total lumen output of 32000lm and a luminous efficiency of 160lm/W.ON-OFF driver. Made in die cast aluminum and finished in Black color. IP66 and IK 08 degree of protection.

| Item code | 86.10018.4451.02 |
|--------------|--|
| Product type | Outdoor |
| Category | Floodlights |
| Family | AQUILA II |
| Pictograms | (→ 50 Hz 220 V)→ SDCM 60 Hz 240 V 350° 3 |
| | CE Driver On Off |
| | IP CRI IK 50000h 66 70 08 L70B50 |

| Product | |
|-----------------------------|-----------------|
| Real power (W) | 200 |
| Real luminous flux (Lm) | 32000 |
| Luminous efficiency (Lm/W) | 160 |
| Beam angle (º) | 55x125°, tilt55 |
| Life time (h) | 50000h L70B50 |
| IP | 66 |
| Electrical class insulation | Class I |
| Colour | Black |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Light source | LED |
| Type of LED | 2835 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | SDCM<5 |
| CRI | ≥70 |
| IK | 08 |

Scheme



